

OTDR Launch Cable 1000M Technical Data Sheet



Product Description

Designed to aid in the testing of fiber optic cable when using an OTDR. The OTDR Launch Fiber box is used with Optical Time Domain Reflectometers (OTDR) to help minimize the effects of the OTDR's launch pulse on measurement uncertainty. Available in many different configurations and fiber lengths.

Product Features

1. Pulse Suppressor, Launch Box, Delay Line, Installation/Testing, Training, Calibration
2. Compound Latch for positive seal and easy opening with locking feature.
3. Nonmetal construction will not dent, corrode, or conduce electricity
4. Water and dust prove allowing the unit to be taken into almost any environment
5. Case can house up to 1000 meters of fiber
6. Auto Purge Valve for changes in altitude and temperature.

Description

Material	SR Polypropylene
Connector type	SC/APC-SC/APC, SC/UPC-SC/UPC, SC/APC-SC/UPC SC/UPC-FC/UPC, SC/UPC-LC/APC, SC/APC-LC/APC SC/APC-FC/APC, SC/APC-LC/UPC, SC/UPC-LC/UPC FC/UPC-LC/UPC, FC/UPC-LC/APC, FC/APC-LC/APC LC/UPC-LC/UPC, SC/APC-FC/UPC, FC/UPC-FC/UPC
Fiber type	Singlemode 9/125, Multimode 62.5/125, Multimode 50/125 OM2, Multimode 50/125 OM3
Typical Loss	< 0.5dB@1310NM for 1000 meters
Size&Weight	25*15*6.5cm; 800g